



VISCOSITY: APPROXIMATE EQUIVALENTS AT SAME TEMPERATURE

Kinematic (Centistokes)	Say bolt Universal (Seconds)	Redwood No.1 (Seconds)	Engler (Degrees)	Say bolt Furol (Seconds)	Redwood No.2 (Seconds)	Kinematic (Centistokes)	Say bolt Universal (Seconds)	Redwood No.1 (Seconds)	Engler (Degrees)	Say bolt Furol (Seconds)	Redwood No.2 (Seconds)
1.8	32	30.8	1.14	-	-	96.8	450	397	12.8	47.0	-
2.7	35	32.2	1.18	-	-	102.2	575	419	13.5	49	-
4.2	40	36.2	1.32	-	-	107.6	500	441	14.2	51	-
5.8	45	40.6	1.46	-	-	118.4	550	485	15.6	56	-
7.4	50	44.9	1.60	-	-	129.2	600	529	17.0	61	-
8.9	55	49.1	1.75	-	-	140.3	650	573	18.5	66	-
10.3	60	53.5	1.88	-	-	151	700	617	19.8	71	-
11.7	65	57.9	2.02	-	-	162	750	661	21.3	76	-
13.0	70	62.3	2.15	-	-	173	800	705	22.7	81	-
14.3	75	67.5	2.31	-	-	183	850	749	24.2	86	-
15.6	80	71.0	2.42	-	-	194	900	793	25.6	91	-
16.8	85	75.1	2.55	-	-	205	950	837	27.0	96	-
18.1	90	79.6	2.68	-	-	215	1,000	882	28.4	100	-
19.2	95	84.2	2.81	-	-	259	1,200	1,058	34.1	121	104
20.4	100	88.4	2.95	-	-	302	1,400	1,234	39.8	141	122
22.8	110	97.1	3.21	-	-	345	1,600	1,411	45.5	160	138
25.0	120	105.9	3.49	-	-	388	1800	1,587	51	180	153
27.4	130	114.8	3.77	-	-	432	2,000	1,763	57	200	170
29.6	140	123.6	4.04	-	-	541	2,500	2,204	71	250	215
31.8	150	132.4	4.32	-	-	650	3,000	2,646	85	300	255
34.0	160	141.1	4.59	-	-	758	3,500	3,087	99	350	300
36.0	170	150.0	4.88	-	-	866	4,000	3,526	114	400	345
38.4	180	158.8	5.15	-	-	974	4,500	3,967	128	450	390
40.6	190	167.5	5.44	-	-	1,082	5,000	4,408	142	500	435
42.8	200	176.4	5.72	23.0	-	1,190	5,500	4,849	156	550	475
47.2	220	194.0	6.28	25.3	-	1,300	6,000	5,290	170	600	515
51.8	240	212	6.85	27.0	-	1,405	6,500	5,730	185	650	580
55.9	260	229	7.38	28.7	-	1,515	7,000	6,171	199	700	600



Kinematic (Centistokes)	Say bolt Universal (Seconds)	Redwood No.1 (Seconds)	Engler (Degrees)	Say bolt Furol (Seconds)	Redwood No.2 (Seconds)	Kinematic (Centistokes)	Say bolt Universal (Seconds)	Redwood No.1 (Seconds)	Engler (Degrees)	Say bolt Furol (Seconds)	Redwood No.2 (Seconds)
60.2	280	247	7.95	30.5	-	1,625	7,500	6,612	213	750	645
64.5	300	265	8.51	32.5	-	1,730	8,000	7,053	227	800	690
69.9	325	287	9.24	35.0	-	1,840	8,500	7,794	242	850	730
75.3	350	309	9.95	37.2	-	1,950	9,000	7,934	256	900	770
80.7	375	331	10.70	39.5	-	2,055	9,500	8,375	270	950	815
36.1	400	353	11.40	42.0	-	2,165	10,000	8,816	284	1,000	855
91.5	425	375	12.10	44.2	-						