



# BEHRAN MOTOR OIL BMB

**High quality multigrade engine oil approved by DAIMLERCHRYSLER AG**

## USES

• **Behran Motor Oil BMB** is a high quality multigrade crankcase lubricant, designed for using in most common passengers car and four-cycle light truck; high performance gasoline; LPG and diesel engines including turbocharged, supercharged and multi valve models, and operates in all types of services including those equipped with exhaust catalytic converters.

## PROPERTIES

• **Behran Motor Oil BMB** meets the requirements of API SJ/CF and compiles with standards of

Mercedes Benz sheet No 229.1.

• **Behran Motor Oil BMB** is available in three SAE viscosity 10W-40 (Semi synthetic), 15W-40 (synthetic blend) and 20W-50 which surpass warranty service requirements for a wide range of gasoline and diesel engines.

• Reduce maintenance costs by controlling deposit build-up in the engine and the turbo-charger, maintains power and economy by protecting the valve train from premature wear.

• Maximizes engine life by resisting the formation of sludge under both low and high temperature conditions and ensures low oil consumption.

## TYPICAL CHARACTERISTICS

Specification	Test Method	10W-40	15W-40	20W-50
Kinematic Viscosity @ 100°C (cSt)	ASTM D-445	15	15.2	19
Viscosity Index	ASTM D-2270	155	140	120
Pour Point °C	ASTM D-97	-30	-27	-24
Flash Point °C	ASTM D-92	220	216	228
Density @ 15°C Kg/m <sup>3</sup>	ASTM D-4052	872	889	885
Total Base Number mg KOH/g	ASTM D-2896	7.5	7.5	7.5

## PERFORMANCE SPECIFICATION

**API SJ/CF/CF-4**



## Packaging

12 x 1 liter plastic containers in one carton

6 x 4 liter plastic containers in one carton

4 x 5 liter plastic containers in one carton

