

BEHRAN DIESEL ENGIN OIL SHPD PLUS

Premium performance all seasons diesel engine oil

USES

- **Behran SHPD Plus** is suitable for high speed four stroke engines to meet 2010 model year on high way exhaust emission standard (higher temperature more EGR), where API CJ-4 is recommended.
- **Behran SHPD Plus** is recommended for use in all applications with diesel fuel ranging in sulfur content up to 500 ppm.

PROPERTIES

- **Behran SHPD Plus** will provide

the latest in protection, including improved wear protection, high temperature oxidation control and soot handling, which will enhance engine durability and cleanliness of engines.

- **Behran SHPD Plus** also protects diesel particulate filters (DPFs) against buildup of harmful deposits. It provides outstanding viscosity control with exceptional product durability.

TYPICAL CHARACTERISTICS

Specification	Test Method	15W-40
Viscosity at 100 °C (cSt)	ASTM D-445	15.4
Viscosity Index	ASTM D-2270	142
Pour Point (min) °C	ASTM D-92	222
Flash Point (max) °C	ASTM D-97	-30
Density @ 15 °C Kg/m ³	ASTM D-4052	865
Total Base Number mg KOH/g	ASTM D-2896	11.5

PERFORMANCE SPECIFICATION

API CJ-4/CI-4 plus/SM/ACEA E7-08, E9-08
Volvo VDS-4, MAN 3575, MB 228.30 & 228.31, RENAULT RLD-3

Packaging

- 20 liter plastic pail
- 208 liter new steel drum

