

# BEHRAN DIESEL ENGINE OIL TURBO EIII

**Long Drain Semi Synthetic Diesel Engine Oil  
approved by DAIMLERCHRYSLER AG**

## USES

- **Behran Turbo EIII 10W-40** is designed for a wide range of high output diesel engines.
- **Behran Turbo EIII** is recommended for a wide range of European high specific output fourcycle diesel engines which are produced with Euro III standards to provide maximum protection in the most severe service conditions, including extended oil drain interval operation.

## PROPERTIES

- **Behran Turbo EIII 10W-40** is approved against Mercedes Benz sheet no. 228.5 and MAN 3277 standards.

- **Behran Turbo EIII** maximizes engine life by preventing bore - polishing, reduces maintenance costs by extending oil drain and engine overhaul periods maintains excellent control of oil consumption, maximizes oil filter life and protects against rust and corrosion.
- **Behran Turbo EIII 10W-40** has very high viscosity index which gives the properties of easy starts, fuel economy, suitable lubrication at high temperature and low oil consumptions.

## TYPICAL CHARACTERISTICS

Specification	Test Method	10W-40
Viscosity at 100 °C (cSt)	ASTM D-445	15.2
Viscosity Index	ASTM D-2270	155
Flash Point (min) °C	ASTM D-92	226
Pour Point (max) °C	ASTM D-97	-33
Density @ 15.5 °C Kg/m <sup>3</sup>	ASTM D-4052	864
Total Base Number mg KOH/g	ASTM D-2896	15.1



## PERFORMANCE SPECIFICATION

**ACEA E4-99, ACEA E5-02, Mack EO-M, Volvo VDS-3, MB 228.5, MAN M3277, MTU TYPE III, scania LDF, Renault RXD**

## Packaging

- 20 liter plastic pail
- 208 liter new steel drum

