

BEHRAN DIESEL ENGINE OIL BXD



USES

• Behran Diesel Engine Oil BXD introduces a common level of performance for the lubrication of highly rated turbo - charged and naturally aspirated diesel engines.

PROPERTIES

• Behran Diesel Engine Oil BXD is made from highly refined base oil, which contains specially selected additive - combination, to ensure engine cleanliness by minimizing high temperature deposits and oil

oxidation. As a result engine performance is maintained at peak for longer periods and so common standards of engine reliabilities are achieved.

• Behran Diesel Engine Oil BXD meets the requirements of API CD/SE and MIL-L-2104D.

• Behran Diesel Engine Oil BXD is available in four SAE viscosity grades: 20W-50, 10W, 30, 40.

• Behran Diesel Engine Oil BXD 20W-50 meets the requirements of MB227.1 too.

TYPICAL CHARACTERISTICS

Specification	Test Method	10W *	30	40	20W-50
Kinematic Viscosity @ 100 °C (cSt)	ASTM D-445	6.3	12	15.5	20
Viscosity Index	ASTM D-2270	104	95	95	122
Pour Point °C	ASTM D-97	-30	-18	-12	-24
Flash Point (COC) °C	ASTM D-92	204	236	240	230
Density @ 15 °C Kg/m ³	ASTM D-4052	882	898	902	896
Total Base Number mg KOH/g	ASTM D-2896	12	12	12	12

PERFORMANCE SPECIFICATION

API CD/SE, MIL-L-2104D

***Allison C3, this grade is formulated for hydraulic systems of construction equipments**

Also this product as BEHRAN GENERATOR OIL for lubrication industrial diesel generators in SAE grades 30,40 and with TBN 12.5 is available.

Packaging

20 liter plastic pail

208 liter new steel drum

