

BEHRAN MOTOR OIL CNG



USES

• **Behran Motor Oil CNG** is a high performance motor oil specially developed for passenger cars used compressed natural Gas (CNG), LPG and Dual fuel.

• **Behran Motor Oil CNG** is a blend of high quality base stocks and advanced additives that available in SAE 20W-50& SAE 10W-40

PROPERTIES

- Extends oil life due to excellent oxidation and nitration resistance
- Optimized level of ash components prolongs the life of valves and spark plugs
- Keeps piston and engine clean thus ensuring smooth engine operation.
- Ensures long and efficient engine operation.

TYPICAL CHARACTERISTICS

Specification	Test Method	10W-40	20W-50
Kinematic Viscosity @ 100°C (cSt)	ASTM D- 445	15.4	19.2
Viscosity Index	ASTM D- 2270	158	124
Pour Point °C	ASTM D- 97	-33	-27
Flash Point (COC) °C	ASTM D- 92	216	220
Density @ 15 °C Kg/m ³	ASTM D- 4052	860	886
Sulfated Ash wt%	ASTM D- 874	0.8	0.8

PERFORMANCE SPECIFICATION

API SL

Packaging

- 12xl liter plastic containers in one carton
- 6x4 liter plastic containers in one carton
- 4x5 liter plastic containers in one carton

