

BEHRAN 2 STROKE OIL M III



USES

- Behran 2 Stroke Oil M III is a low ash oil for outboard water-cooled two stroke engine designed to meet the critical requirements.

PROPERTIES

- Excellent thermal and oxidation stability
- Excellent cleaning properties and

deposit control

- provides rust protection while allowing for maximum output of engine power
- Recommended fuel/oil ratio in new engines at sealing period (25:1) & after it (50:1)
- Not suitable for 4-stroke gasoline or diesel engines

TYPICAL CHARACTERISTICS

Specification		Test Method	Result
Kinematic Viscosity @ 100°C (cSt)		ASTM D-445	9.5
Viscosity Index		ASTM D-2270	115
Pour Point	°C	ASTM D-97	-30
Flash Point (COC)	°C	ASTM D-92	-
Density @ 15 °C	Kg/m ³	ASTM D- 4052	878
Total Base Number	mg KOH/g	ASTM D-2896	8.8
Sulfated Ash	wt%	ASTM D- 874	0.01

PERFORMANCE SPECIFICATION

NMMA(National Marine Manufacturers Association) TC-W3 with M/F grade II

Packaging

12x1 liter plastic containers
in one carton

6x4 liter plastic containers
in one carton

4x5 liter plastic containers
in one carton

