



BEHRAN ATF VI

Automatic Transmission Fluid

USES

- **Behran ATF VI** is high performance, synthetic blend automatic transmission fluid.
- **Behran ATF VI** provides warranty protection for 2006 and newer GM vehicles.
- **Behran ATF VI** protects all General Motors car and is an exceptional automatic transmission designed to meet the stringent service fill requirements of GM'S Dexron VI specification and trucks that require DEXRON VI , DEXRON III and , DEXRON II.

provide smooth gear shifting low temperature operation and help prevent transmission vibration.

- Outstanding resistance against sludge and deposit formation
- Improved anti wear protection which contributes to extend transmission life
- Outstanding low temperature performance



PROPERTIES

- Extended fluid life
- Improved oxidation and thermal stability versus DEXRON III
- Optimized frictional properties that

TYPICAL CHARACTERISTICS

Specification	Test Method	Result
Kinematic Viscosity @ 40°C (cSt) @ 100 °C (cSt)	ASTM D-445	30.2 6.1
Viscosity Index	ASTM D-2270	155
Pour Point °C	ASTM D-97	-45
Flash Point (COC) °C	ASTM D-92	190
Desity @ 15 °C kg/m³	ASTM D-4052	846
Brookfield Viscosity @ -40°C CP max	ASTM D-2983	15000

PERFORMANCE SPECIFICATION

General Motors Dexron VI

Packaging

12×1 liter plastic containers in one carton

6×4 liter plastic containers in one carton

208 liter new steel drum

