



BEHRAN GEAR OIL GL - 4

USES

- Behran Gear Oil GL- 4 is a high performance universal gear lubricant for manual transmission, steering gears and other gearboxes of automotive equipment.
- Behran Gear Oil GL- 4 also is suitable for most worm-gear drives.

- Low pour point
- Good corrosion protection



PROPERTIES

- Good load carrying ability for intended services
- High oxidation stability

TYPICAL CHARACTERISTICS

Specification	Test Method	75W	75W-80	75W-90	80W	80W-90	85W-90	85W-140
Kinematic Viscosity @100°C (cSt)	ASTM D-445	5.5	8.5	16	9.5	15	16.5	24.5
Viscosity Index	ASTM D-2270	100	160	187	90	120	85	92
Pour Point °C	ASTM D-97	-27	-36	-36	-30	-30	-18	-15
Flash Point (COC) °C	ASTM D-92	196	200	202	220	210	226	230
Density @ 15 °C Kg/m ³	ASTM D-4052	878	870	880	890	900	911	907

PERFORMANCE SPECIFICATION

API GL-4

Also "GL4-MB "is available in SAE grades 80W-90 and 85W-90 that meet the requirements of Mercedes Benz 235.1 and approved by DaimlerChrysler and ZF.



Packaging

12 x 1 liter plastic containers in one carton

6 x 4 liter plastic containers in one carton

20 liter plastic pail

208 liter new steel drum

