

SYSTEM CERTIFICATION

www.behranoil.com , E-mail: export@behranoil.com



Fax: +98 21 22284302

BEHRAN HYDRAULIC HP

- **Behran Hydraulic HP** Oils are premium quality hydraulic oils with rapid air release and high filterability characteristics.
- **Behran Hydraulic HP** is suitable for systems containing soft metals as silver and bronze.

TYPICAL CHARACTERISTICS

Specification	Test Method	HP32	HP46	HP68	HP100	HP150
Kinematic Viscosity @ 40 °C cSt @ 100 °C cSt	ASTM D-445	32	46	68	100	150
		5.5	7	8.5	11	14.5
Viscosity Index	ASTM D-2270	100	97	96	95	95
Pour Point	ASTM D-97	-30	-27	-24	-21	-18
Flash Point (COC)	ASTM D-92	204	208	216	234	240
Density @ 15 °C Kg/m ³	ASTM D-4052	874	880	883	885	888

PERFORMANCE SPECIFICATION

DIN 51524 part II (HLP), Denison HF-O

Note

*It is recommended to avoid contamination of Hydraulic oils , with other products, particularly with detergent-type oils which could lead to operational difficulties such as filter plugging or foaming.

Packaging

208 liter new steel drum

