



### BEHRAN HYDRAULIC T

- Behran Hydraulic T oils are high viscosity index hydraulic oils which ensure excellent viscosity characteristic over a wide temperature range.
- Behran Hydraulic T meets the requirements of DIN 51524 part III (HVLP), Denison HF-O.

### BEHRAN HYDRAULIC TX

- Behran Hydraulic TX oil is a very high viscosity index hydraulic oil with good anti wear property, long term oxidation stability and excellent filterability.
- Behran Hydraulic TX oil meets the requirement of DIN 51524 part III (HVLP), Denison HF-O.

### TYPICAL CHARACTERISTICS

Specification	Test Method	T15	T22	T32	T37	T46	T68	T100
Kinematic Viscosity @ 40 °C cSt	ASTM D-445	15	22	32	37	46	68	100
		3.8	5.8	6	6.5	9.5	11	15
Viscosity Index	ASTM D-2270	150	150	150	150	150	150	150
Pour Point °C	ASTM D-97	-42	-30	-30	-30	-30	-30	-30
Flash Point (coc) °C	ASTM D-92	146	180	186	190	206	218	220
Density@15 °C Kg/m <sup>3</sup>	ASTM D-4052	878	860	865	874	875	878	884

### TYPICAL CHARACTERISTICS

Specification	Test Method	TX32	TX46
Kinematic Viscosity @ 40 °C cSt	ASTM D-445	32	46
		7.3	9
Viscosity Index	ASTM D-2270	190	190
Pour Point °C	ASTM D-97	-36	-30
Flash Point (COC) °C	ASTM D-92	160	190
Density@15 °C Kg/m <sup>3</sup>	ASTM D-4052	870	872

### Packaging

208 liter new steel drum

