



BEHRAN MULTIPURPOSE LITHIUM GREASE

USES

- Lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal.
- General lubrication of vehicles with no particular Extreme- Pressure requirements.
- Can be used in all lubrication systems.
- Range of use - 20°C to 120°C.



PROPERTIES

- Suitable for long-term greasing
- Very good thermal , oxidation & mechanical stability
- Good water washout resistance
- Effective rust and corrosion protection

TYPICAL CHARACTERISTICS

Specification	Unit	Test Method	Behran Lithium Grease		
Texture	-	-	smooth		
Thickener Type	Visual	-	lithium soap		
Color	Visual	-	white-brown		
Base Oil	-	-	Solvent Refind Mineral Oil		
NLGI	grade	-	1	2	3
Penetration, Worked	0.1mm	ASTM D-217	310-340	265-295	220-250
Dropping Point	°C	ASTM D-566	190-200	190-200	190-200



CLASSIFICATION

- BEHRAN MULTIPURPOSE LITHIUM GREASE 1,2,3 (ISO L-X-BCDA 1,2,3)

Packaging

- 24×453 gr plastic containers in one carton
- 24×900 gr plastic containers in one carton
- 4×4.5 kg pails in one carton
- 15 kg (Lug)
- 55 kg(Keg)
- 180 kg drum

