



BEHRAN CALCIUM GREASE L,D

Grease for general greasing

USES

- Non staining grease for the lubrication of car body fittings.
- Marine and agricultural applications.
- Working temperature in the range 20°C to 70°C.
- Water resistance grease recommended for general lubrications.



PROPERTIES

- Excellent Corrosion protection in the presence of water
- Good pump ability
- Very Good Water Resistance properties

TYPICAL CHARACTERISTICS

Specification	Unit	Test Method	Behran Calcium Grease L			Behran Calcium Grease D	
Texture	-	-	smooth			smooth	
Thickener Type	-	-	Calcium soap			Calcium soap	
Color	Visual	-	White-yellow			brown	
Base Oil	-	-	Solvent Refind Mineral Oil			Solvent Refind Mineral Oil	
NLGI	grade	-	1	2	3	2	3
Penetration, Worked	0.1mm	ASTM D-217	310-340	265-295	220-250	265-295	220-250
Dropping Point	°C	ASTM D-566	95	95	95	93-96	93-96

CLASSIFICATION

BEHRAN CALCIUM GREASE L1,2,3 (ISO L-X-BADA 1,2,3)

BEHRAN CALCIUM GREASE D 2,3 (ISO L-X-BADA 2,3)

Packaging

24×453 gr plastic containers
in one carton

24×900 gr plastic containers
in one carton

4×4.5 kg pails in one carton

15 kg (Lug)

