



# BEHRAN CALCIUM COMPLEX GREASE

## USES

- Very adhesive grease.
- Recommended for the lubrication of wire ropes metal cables, chains, slide rail and open gears found in marine off-shore and industrial applications.
- Range of use-20 °c to 150 °c
- High temperature resistance and excellent resistance to water for general lubrication under very severe conditions (heavy loads, shocks, vibrations, dust and water).



## PROPERTIES

- High Dropping point
- Good EP properties
- A suitable economic alternative in most of greasing

## TYPICAL CHARACTERISTICS

Specification	Unit	Test Method	Behran Calcium Complex Grease		
Texture	-	-	smooth		
Thickener Type	-	-	Calcium complex soap		
Color	-	-	brown		
Base Oil	-	-	Solvent Refind Mineral Oil		
NLGI	grade	-	2	3	4
Penetration, Worked	0.1mm	ASTM D-217	265-295	220-250	175-205
Dropping Point	°C	ASTM D-566	260	260	260

## CLASSIFICATION

**BEHRAN CALCIUM COMPLEX GREASE 2,3,4 (ISO L-X-BDAA 2,3,4)**

## Packaging

- 24×453 gr plastic containers in one carton
- 24×900 gr plastic containers in one carton
- 4×4.5 kg pails in one carton
- 15 kg (Lug)
- 55 kg(Keg)
- 180 kg drum

