BEHRAN COOLANT

Ready to use 50/50 Prediluted Coolant

Fax: 498 21 22 Registration of the second of

USES

• Behran Coolant is all season 50/50 pre diluted coolant (a blend of 50% antifreeze / coolant) for temperature and corrosion protection and farm tracks

PROPERTIES

 It provides protection against radiator freeze up down to -37 °C and boils over to 108℃

- This product protects coolant system metals, uncluding aluminum, against piting caused by cavitations and corrosion.
- This coolant will provide up to, 60000Km or 2 years service life.
- It is ready for use, DO NOT ADD WATER

TYPICAL CHARACTERISTICS

Specification	Test Method	BEHRAN COOLANT	*BEHRAN COOLANT 65
Desity @ 15 °C Kg/m³	ASTM D-1122	1066	1075
Freezing point °C	ASTM D-1177	-37	-63
Boilling point °C	ASTM D-1120	108	114
Color	-	Light green	Light green
PH	ASTM D-1287	7.5	8.12
Reserve alkalinity(ml 0.1N HCL)	ASTM D-1121	3	10.1

PERFORMANCE SPECIFICATION

ASTM D-3306, and complies with ISIRI No.338

* Also BEHRAN COOLANT 65 for cold climates with OAT technology is available that meets the requirements of Gost 28084-89 and ASTM 3306.

Packaging

6×4 liter plastic containers in one carton 4×5 liter plastic containers in one carton 20 liter plastic pail

